django-safedelete Documentation Release 0.4

palkeo

Oct 03, 2022

Contents

1	What is it ?	3					
2	Example	5					
3	Compatibilities						
4	Installation						
5	Configuration						
6	Documentation 6.1 Model 6.2 Managers 6.3 OuervSet	13 13 16 18					
	6.4 Signals Signals Signals 6.5 Handling administration Signals Signals	19 20					
Ру	Python Module Index						
Inc	Index						



What is it ?

For various reasons, you may want to avoid deleting objects from your database.

This Django application provides an abstract model, that allows you to transparently retrieve or delete your objects, without having them deleted from your database.

You can choose what happens when you delete an object :

- it can be masked from your database (soft delete, the default behavior)
- it can be masked from your database and mask any dependent models. (cascading soft delete)
- it can be normally deleted (hard delete)
- it can be hard-deleted, but if its deletion would delete other objects, it will only be masked
- it can be never deleted or masked from your database (no delete, use with caution)

Example

```
# imports
from safedelete.models import SafeDeleteModel
from safedelete.models import HARD_DELETE_NOCASCADE
# Models
# We create a new model, with the given policy : Objects will be hard-deleted, or_
\hookrightarrow soft deleted if other objects would have been deleted too.
class Article(SafeDeleteModel):
   _safedelete_policy = HARD_DELETE_NOCASCADE
   name = models.CharField(max_length=100)
class Order(SafeDeleteModel):
   _safedelete_policy = HARD_DELETE_NOCASCADE
   name = models.CharField(max_length=100)
    articles = models.ManyToManyField(Article)
# Example of use
>>> article1 = Article(name='article1')
>>> article1.save()
>>> article2 = Article(name='article2')
>>> article2.save()
>>> order = Order(name='order')
>>> order.save()
>>> order.articles.add(article1)
# This article will be masked, but not deleted from the database as it is still_
\rightarrow referenced in an order.
```

(continues on next page)

(continued from previous page)

```
>>> article1.delete()
# This article will be deleted from the database.
>>> article2.delete()
```

Compatibilities

- Branch 0.2.x is compatible with django >= 1.2
- Branch 0.3.x is compatible with django >= 1.4
- Branch 0.4.x is compatible with django >= 1.8
- Branch 0.5.x is compatible with django >= 1.11
- Branch 1.0.x, 1.1.x and 1.2.x are compatible with django ≥ 2.2
- Branch 1.3.x is compatible with django >= 3.2 and Python >= 3.7

Current branch (1.3.x) is tested with :

- Django 3.2 using python 3.7 to 3.10.
- Django 4.0 using python 3.8 to 3.10.
- Django 4.1 using python 3.8 to 3.10.

Installation

Installing from pypi (using pip).

pip install django-safedelete

Installing from github.

```
pip install -e git://github.com/makinacorpus/django-safedelete.git#egg=django-

→safedelete
```

Add safedelete in your INSTALLED_APPS:

```
INSTALLED_APPS = [
    'safedelete',
    [...]
]
```

The application doesn't have any special requirement.

Configuration

In the main django settings you can activate the boolean variable SAFE_DELETE_INTERPRET_UNDELETED_OBJECTS_AS_CREAT If you do this the update_or_create() function from django's standard manager class will return True for the created variable if the object was soft-deleted and is now "revived".

By default, the field that indicates a database entry is soft-deleted is deleted, however, you can override the field name using the SAFE_DELETE_FIELD_NAME setting.

Documentation

6.1 Model

6.1.1 Built-in model

class safedelete.models.**SafeDeleteModel**(*args, **kwargs) Abstract safedelete-ready model.

Note: To create your safedelete-ready models, you have to make them inherit from this model.

- Attribute deleted DateTimeField set to the moment the object was deleted. Is set to None if the object has not been deleted.
- Attribute deleted_by_cascade BooleanField set True whenever the object is deleted due cascade operation called by delete method of any parent Model. Default value is False. Later if its parent model calls for cascading undelete, it will restore only child classes that were also deleted by a cascading operation (deleted_by_cascade equals to True), i.e. all objects that were deleted before their parent deletion, should keep deleted if the same parent object is restored by undelete method.

If this behavior isn't desired, class that inherits from SafeDeleteModel can override this attribute by setting it as None: overriding model class won't have its deleted_by_cascade field and won't be restored by cascading undelete even if it was deleted by a cascade operation.

```
>>> class MyModel(SafeDeleteModel):
... deleted_by_cascade = None
... my_field = models.TextField()
```

Attribute_safedelete_policy define what happens when you delete an object. It can be one of HARD_DELETE, SOFT_DELETE, SOFT_DELETE_CASCADE, NO_DELETE and HARD_DELETE_NOCASCADE. Defaults to SOFT_DELETE.

- Attribute objects The safedelete.managers.SafeDeleteManager returns the nondeleted models.
- Attribute all_objects The safedelete.managers.SafeDeleteAllManager returns all the models (non-deleted and soft-deleted).
- Attribute deleted_objects The safedelete.managers.SafeDeleteDeletedManager returns the soft-deleted models.

```
save (keep_deleted=False, **kwargs)
```

Save an object, un-deleting it if it was deleted.

Args: keep_deleted: Do not undelete the model if soft-deleted. (default: {False}) kwargs: Passed onto *save()*.

Note: Undeletes soft-deleted models by default.

undelete (*force_policy: Optional[int]* = *None*, ***kwargs*) \rightarrow Tuple[int, Dict[str, int]] Undelete a soft-deleted model.

Args: force_policy: Force a specific undelete policy. (default: {None}) kwargs: Passed onto save().

Note: Will raise a AssertionError if the model was not soft-deleted.

```
classmethod has_unique_fields() \rightarrow bool
```

Checks if one of the fields of this model has a unique constraint set (unique=True).

It also checks if the model has sets of field names that, taken together, must be unique.

Args: model: Model instance to check

```
class safedelete.models.SafeDeleteMixin(*args, **kwargs)
```

SafeDeleteModel was previously named SafeDeleteMixin.

Deprecated since version 0.4.0: Use *SafeDeleteModel* instead.

6.1.2 Policies

You can change the policy of your model by setting its _safedelete_policy attribute. The different policies are:

safedelete.models.HARD_DELETE

This policy will:

• Hard delete objects from the database if you call the delete() method.

There is no difference with « normal » models, but you can still manually mask them from the database, for example by using obj.delete(force_policy=SOFT_DELETE).

safedelete.models.SOFT_DELETE

This policy will:

This will make the objects be automatically masked (and not deleted), when you call the delete() method. They will NOT be masked in cascade.

safedelete.models.SOFT_DELETE_CASCADE

This policy will:

This will make the objects be automatically masked (and not deleted) and all related objects, when you call the delete() method. They will be masked in cascade.

safedelete.models.HARD_DELETE_NOCASCADE

This policy will:

- Delete the object from database if no objects depends on it (e.g. no objects would have been deleted in cascade).
- Mask the object if it would have deleted other objects with it.

safedelete.models.NO_DELETE

This policy will:

• Keep the objects from being masked or deleted from your database. The only way of removing objects will be by using raw SQL.

6.1.3 Policies Delete Logic Customization

Each of the policies has an overwritable function in case you need to customize a particular policy delete logic. The function per policy are as follows:

Policy	Overwritable Function
SOFT_DELETE	soft_delete_policy_action
HARD_DELETE	hard_delete_policy_action
HARD_DELETE_NOCASCADE	hard_delete_cascade_policy_action
SOFT_DELETE_CASCADE	soft_delete_cascade_policy_action

Example:

To add custom logic before or after the execution of the original delete logic of a model with the policy SOFT_DELETE you can overwrite the soft_delete_policy_action function as such:

```
def soft_delete_policy_action(self, **kwargs):
    # Insert here custom pre delete logic
    delete_response = super().soft_delete_policy_action(**kwargs)
    # Insert here custom post delete logic
    return delete_response
```

6.1.4 Fields uniqueness

Because unique constraints are set at the database level, set *unique=True* on a field will also check uniqueness against soft deleted objects. This can lead to confusion as the soft deleted objects are not visible by the user. This can be solved by setting a partial unique constraint that will only check uniqueness on non-deleted objects:

```
class Post (SafeDeleteModel):
    name = models.CharField(max_length=100)
class Meta:
    constraints = [
        UniqueConstraint(
            fields=['name'],
                condition=Q(deleted_isnull=True),
                name='unique_active_name'
            ),
        ]
```

6.2 Managers

6.2.1 Built-in managers

```
class safedelete.managers.SafeDeleteManager (queryset_class: Op-
tional[Type[safedelete.queryset.SafeDeleteQueryset]]
= None)
```

Default manager for the SafeDeleteModel.

If _safedelete_visibility == DELETED_VISIBLE_BY_PK, the manager can returns deleted objects if they are accessed by primary key.

Attribute_safedelete_visibility define what happens when you query masked objects. It can be one of DELETED_INVISIBLE and DELETED_VISIBLE_BY_PK. Defaults to DELETED_INVISIBLE.

```
>>> from safedelete.models import SafeDeleteModel
>>> from safedelete.managers import SafeDeleteManager
>>> class MyModelManager(SafeDeleteManager):
... __safedelete_visibility = DELETED_VISIBLE_BY_PK
...
>>> class MyModel(SafeDeleteModel):
... __safedelete_policy = SOFT_DELETE
... my_field = models.TextField()
... objects = MyModelManager()
...
```

Attribute _queryset_class define which class for queryset should be used This attribute allows to add custom filters for both deleted and not deleted objects. It is SafeDeleteQueryset by default. Custom queryset classes should be inherited from SafeDeleteQueryset.

get_queryset()

Return a new QuerySet object. Subclasses can override this method to customize the behavior of the Manager.

all_with_deleted () \rightarrow django.db.models.query.QuerySet Show all models including the soft deleted models.

Note: This is useful for related managers as those don't have access to all_objects.

Note: This is useful for related managers as those don't have access to deleted_objects.

all (***kwargs*) \rightarrow django.db.models.query.QuerySet

Pass kwargs to SafeDeleteQuerySet.all().

Args: force_visibility: Show deleted models. (default: {None})

Note: The force_visibility argument is meant for related managers when no other managers like all_objects or deleted_objects are available.

update_or_create (*defaults=None*, ***kwargs*) \rightarrow Tuple[django.db.models.base.Model, bool] See ().

Change to regular djangoesk function: Regular update_or_create() fails on soft-deleted, existing record with unique constraint on non-id field If object is soft-deleted we don't update-or-create it but reset the deleted field to None. So the object is visible again like a create in any other case.

Attention: If the object is "revived" from a soft-deleted state the created return value will still be false because the object is technically not created unless you set SAFE_DELETE_INTERPRET_UNDELETED_OBJECTS_AS_CREATED = True in the django settings.

Args: defaults: Dict with defaults to update/create model instance with kwargs: Attributes to lookup model instance with

static get_soft_delete_policies()

Returns all states which stand for some kind of soft-delete

```
class safedelete.managers.SafeDeleteAllManager(queryset_class: Op-
```

tional[Type[safedelete.queryset.SafeDeleteQueryset]] = None)

SafeDeleteManager with _safedelete_visibility set to DELETED_VISIBLE.

Note: This is used in safedelete.models.SafeDeleteModel.all_objects.

```
class safedelete.managers.SafeDeleteDeletedManager (queryset_class: Op-
tional[Type[safedelete.queryset.SafeDeleteQueryset]]
= None)
```

SafeDeleteManager with _safedelete_visibility set to DELETED_ONLY_VISIBLE.

Note: This is used in safedelete.models.SafeDeleteModel.deleted_objects.

6.2.2 Visibility

A custom manager is used to determine which objects should be included in the querysets.

class safedelete.managers.**SafeDeleteManager**(*queryset_class: Op-*

tional[Type[safedelete.queryset.SafeDeleteQueryset]]
= None)

Default manager for the SafeDeleteModel.

If _safedelete_visibility == DELETED_VISIBLE_BY_PK, the manager can returns deleted objects if they are accessed by primary key.

Attribute safedelete visibility define what happens when you query masked objects. It can be one of DELETED INVISIBLE and DELETED VISIBLE BY PK. Defaults to DELETED INVISIBLE.

```
>>> from safedelete.models import SafeDeleteModel
>>> from safedelete.managers import SafeDeleteManager
>>> class MyModelManager(SafeDeleteManager):
        _safedelete_visibility = DELETED_VISIBLE_BY_PK
. . .
. . .
>>> class MyModel (SafeDeleteModel):
        _safedelete_policy = SOFT_DELETE
. . .
        my_field = models.TextField()
. . .
        objects = MyModelManager()
. . .
. . .
>>>
```

Attribute _queryset_class define which class for queryset should be used This attribute allows to add custom filters for both deleted and not deleted objects. It is SafeDeleteQueryset by default. Custom queryset classes should be inherited from SafeDeleteQueryset.

If you want to change which objects are "masked", you can set the _safedelete_visibility attribute of the manager to one of the following:

```
safedelete.managers.DELETED INVISIBLE
```

This is the default visibility.

The objects marked as deleted will be visible in one case : If you access them directly using a OneToOne or a ForeignKey relation.

For example, if you have an article with a masked author, you can still access the author using article. author. If the article is masked, you are not able to access it using reverse relationship : author. article set will not contain the masked article.

safedelete.managers.DELETED VISIBLE BY FIELD

This policy is like DELETED_INVISIBLE, except that you can still access a deleted object if you call the get() or filter() function, passing it the default field pk parameter. Configurable through the _safedelete_visibility_field attribute of the manager.

So, deleted objects are still available if you access them directly by this field.

6.3 QuerySet

6.3.1 Built-in QuerySet

```
class safedelete.gueryset.SafeDeleteQueryset(model:
                                                                                             Op-
                                                          tional[Type[django.db.models.base.Model]]
                                                                 None,
                                                                             query:
                                                                                             Op-
                                                          =
                                                          tional[safedelete.query.SafeDeleteQuery]
                                                                                Optional[str] =
                                                          = None,
                                                                      using:
                                                          None.
                                                                    hints:
                                                                                Optional[Dict[str,
                                                          django.db.models.base.Model]] = None)
```

Default queryset for the SafeDeleteManager.

Takes care of "lazily evaluating" safedelete QuerySets. QuerySets passed within the SafeDeleteQueryset will have all of the models available. The deleted policy is evaluated at the very end of the chain when the QuerySet itself is evaluated.

delete (*force_policy: Optional[int]* = *None*) \rightarrow Tuple[int, Dict[str, int]] Overrides bulk delete behaviour.

Note: The current implementation loses performance on bulk deletes in order to safely delete objects according to the deletion policies set.

See also:

```
safedelete.models.SafeDeleteModel.delete()
```

undelete (*force_policy: Optional[int]* = *None*) \rightarrow Tuple[int, Dict[str, int]] Undelete all soft deleted models.

Note: The current implementation loses performance on bulk undeletes in order to call the pre/post-save signals.

See also:

safedelete.models.SafeDeleteModel.undelete()

all (*force_visibility=None*) \rightarrow _QS

Override so related managers can also see the deleted models.

A model's m2m field does not easily have access to *all_objects* and so setting *force_visibility* to True is a way of getting all of the models. It is not recommended to use *force_visibility* outside of related models because it will create a new queryset.

Args: force_visibility: Force a deletion visibility. (default: {None})

```
filter (*args, **kwargs)
```

Return a new QuerySet instance with the args ANDed to the existing set.

6.4 Signals

6.4.1 Signals

There are two signals available. Please refer to the Django signals documentation on how to use them.

safedelete.signals.pre_softdelete

Sent before an object is soft deleted.

safedelete.signals.post_softdelete

Sent after an object has been soft deleted.

safedelete.signals.post_undelete

Sent after a deleted object is restored.

6.5 Handling administration

6.5.1 Model admin

Deleted objects will also be hidden in the admin site by default. A ModelAdmin abstract class is provided to give access to deleted objects.

An undelete action is provided to undelete objects in bulk. The deleted attribute is also excluded from editing by default.

You can use the highlight_deleted method to show deleted objects in red in the admin listing.

You also have the option of using highlight_deleted_field which is similar to highlight_deleted, but allows you to specify a field for sorting and representation. Whereas highlight_deleted uses your object's __str__ function to represent the object, highlight_deleted_field uses the value from your object's specified field.

To use highlight_deleted_field, add "highlight_deleted_field" to your list filters (as a string, seen in the example below), and set *field_to_highlight = "desired_field_name"* (also seen below). Then you should also set its short description (again, see below).

class safedelete.admin.**SafeDeleteAdmin** (*model*, *admin_site*) An abstract ModelAdmin which will include deleted objects in its listing.

Example

```
>>> from safedelete.admin import SafeDeleteAdmin,_

    SafeDeleteAdminFilter, highlight_deleted

>>> class ContactAdmin(SafeDeleteAdmin):

    ... list_display = (highlight_deleted, "highlight_deleted_field",

    ... fist_filter = ("last_name", "email") + SafeDeleteAdmin.list_display

    ... list_filter = ("last_name", SafeDeleteAdminFilter,) +_

    ... SafeDeleteAdmin.list_filter

    ... field_to_highlight = "id"

    ... ContactAdmin.highlight_deleted_field.short_description =_

    ... GontactAdmin.field_to_highlight
```

Python Module Index

S

safedelete.admin, 20
safedelete.managers, 16
safedelete.models, 13
safedelete.queryset, 18
safedelete.signals, 19

Index

Α

all() (<i>safedelete.managers.SafeDeleteManager</i> <i>method</i>), 17	<pre>safedelete.admin(module), 20 safedelete.managers(module), 16</pre>		
all() (safedelete.queryset.SafeDeleteQueryset	safedelete.models (<i>module</i>), 13		
method), 19	safedelete.queryset (module), 18		
all_with_deleted()	safedelete.signals(module),19		
(safedelete.managers. SafeDeleteManager)	<pre>safedelete.signals.post_softdelete</pre>		
method), 16	module safedelete.signals), 19		
П	<pre>safedelete.signals.post_undelete(in n</pre>		
D	ule safedelete.signals), 19		
delete() (safedelete.queryset.SafeDeleteQueryset	<pre>safedelete.signals.pre_softdelete</pre>		
method), 19	module safedelete.signals), 19		
DELETED_INVISIBLE (in module	SafeDeleteAdmin (class in safedelete.admin), 20		
safedelete.managers), 18	SafeDeleteAllManager (class		
<pre>deleted_only() (safedelete.managers.SafeDeleteManagers.Saf</pre>	ager safedelete.managers), 17		
method), 16	SafeDeleteDeletedManager (class		
DELETED_VISIBLE_BY_FIELD (in module	safedelete.managers), 17		
safedelete.managers), 18	SafeDeleteManager (class in safedelete.manage		
F	16		
1	SafeDeleteMixin (<i>class in safedelete.models</i>), 1- SafeDeleteModel (<i>class in safedelete.models</i>), 1- SafeDeleteQueryset (<i>class in safedelete.query</i>)		
filter() (safedelete.queryset.SafeDeleteQueryset			
method), 19			

G

get_queryset() (safedelete.managers.SafeDeleteMan method), 16 get_soft_delete_policies() (safedelete.managers.SafeDeleteManager static method), 17

Η

HARD_DELETE (in module safedelete.models), 14 HARD_DELETE_NOCASCADE (in module safedelete.models), 15 has_unique_fields() (safe delete.models. Safe Delete Modelclass method), 14

Ν

NO_DELETE (in module safedelete.models), 15

S

		· · · · · · · · · · · · · · · · · · ·	<i>, ,</i>					
safe	delete.	managers	(module), 1	6				
safedelete.models(<i>module</i>),13								
safedelete.queryset (module), 18								
safe	delete.	signals(<i>r</i>	nodule), 19					
safe	delete.	signals.p	post_sof	tdelete	e (in			
	module	e safedelete.s	signals), 19					
safedelete.signals.post_undelete (in mod								
	ule saf	edelete.signa	uls), 19					
safe	delete.	signals.p	pre_soft	delete	(in			
	module	e safedelete.s	signals), 19					
SafeI	SafeDeleteAdmin (class in safedelete.admin), 20							
SafeI	DeleteA	llManage	r i	(class	in			
nager	safedel	lete.manager	·s), 17					
SafeI	DeleteD	eletedMar	nager	(class	in			
	safedel	lete.manager	·s), 17					
SafeI	DeleteM	anager (<i>cl</i>	ass in safed	delete.mar	agers),			
	16							
SafeI	DeleteM	ixin (<i>class</i>	in safedele	te.models), 14			
SafeI	SafeDeleteModel (class in safedelete.models), 13							
SafeDeleteQueryset (class in safedelete.queryset),								
	18							
save	() (safed	elete.models	.SafeDelete	eModel m	ethod),			
nager	14							
SOFT_	_DELETE	(in module s	safedelete.n	iodels), 14	1			
SOFT_	_DELETE	_CASCADE	(in	ı	module			
	safedel	lete.models),	15					

U

(safe delete.models. Safe Delete Modelundelete() method), 14 undelete() (safedelete.queryset.SafeDeleteQueryset method), 19 update_or_create() (safe delete.managers. Safe Delete Managermethod), 17